

2/PRT3

09/857911

JC03 Rec'd PCT/PTO 11 JUN 2001

GR 98 P 5897

- 1 -

Description

Mobile communications terminal

- 5 The present invention relates to a mobile communications terminal, in particular a mobile telephone, according to the preamble to claim 1.

- Mobile communications terminals and mobile telephones
10 have a display to present different types of information. This information may, for example, relate to the mobile radio network operator, the battery level, the telephone number or text information transmitted during a communications link. In
15 conventional mobile telephones, this display is designed in the form of a black-and-white liquid crystal display. More recent equipment already has, in some cases, a color graphics display.
- 20 Due to advancing further development of existing mobile radio networks and the introduction of correspondingly more powerful mobile radio systems, mobile communications terminals are increasingly equipped with multimedia user facilities. Third-generation mobile
25 radio systems are generally referred to by the term UMTS (Universal Mobile Telecommunication System). Due to the development of UMTS, voice, graphics, video and other broadband services are intended to be combined with one another and offered to subscribers, with the
30 aim of producing a worldwide, universal mobile radio standard. This means that these communications services are intended to be offered to every subscriber, regardless of his current location, the network in which he is currently located, or the terminal which he
35 is currently using.

A substantial component of the desired UMTS mobile radio standard, which is to be introduced from 2001, is

09/857911-001300

GR 98 P 5897

- 1a -

represented by the aforementioned implementation of
multimedia user facilities, i.e. a comprehensive

00857911.091301

and flexible range of services comprising voice, data and image transmission is to be provided. Videotelephony or Internet access, for example, are also intended to be provided.

5 However, corresponding mobile communications terminals
must be equipped with color displays for multimedia
user facilities of this type, although these, even in
non-illuminated mode, have a relatively high power
10 consumption, given that a power of several times 10 mW
is required simply to refresh the color pixel matrix of
such color displays. In any case, even in standby mode,
i.e. when no communications link exists, specific user
information must be displayed to inform the user, for
15 example, of a link to the mobile radio network operator
or the battery level of the mobile terminal, etc. The
use of conventional color displays would therefore
substantially reduce the standby time, whereas the aim
is to prevent this.

20 The aforementioned problem could be eliminated by providing two different displays, a color display being used to present multimedia communications information and a conventional display being used to present the
25 aforementioned miscellaneous user and standby information. However, this solution would result in a disadvantageous increase in production costs and space requirement.

30 The object of the present invention is therefore to
propose a mobile communications terminal in which the
aforementioned problem is eliminated. In particular, a
mobile communications terminal is to be created which,
on the one hand, is suitable for operation in mobile
35 radio networks with multimedia user facilities and
which, on the other hand, minimizes power consumption
for the presentation of corresponding information on a
display of the mobile communications terminal.